

MORE POWER – LESS SPACE™



HIGH RATE SERIES

HR3000

- **Exclusive IPF® Technology optimizes power capacity, cell consistency, and long-term reliability**
- Advanced AGM technology for superior high rate, short term power
- Reinforced case resists bulging and meets safety requirements
- Case & cover heat sealed and 100% tested to prevent leaks
- Epoxy-sealed posts eliminate leaks
- Puncture resistant micro-porous glass mat separators extend life
- Flame arresting, low pressure, self-sealing valves are 100% factory tested
- Computer-aided design, manufacturing control processes, and standards to ensure quality products
- All batteries meet or exceed IEEE recommended practices
- Battery design and construction meet UL recognition requirements



QUALITY SYSTEM CERTIFIED
ISO 9001
ISO/TS 16949
 ENVIRONMENTAL SYSTEM CERTIFIED
ISO 14001



SPECIFICATIONS

Nominal Voltage: 12-Volt/310 w.p.c.
 @ 15 min. rate to 1.67 v.p.c.

Positive Plate: Pure lead, low-calcium, high-tin alloy

Negative Plate: Lead calcium alloy

Post Seal: Epoxy-sealed

Terminal: Top access,
 1/4" - 20 threaded insert

Container: Flame-retardant, polypropylene -
 UL 94 V-0/>28% L.O.I.

Safety Vent: Low positive pressure,
 self-sealing w/ flame arrestor

Float Voltage: 2.25 v.p.c. ± 0.01 v.p.c. (Range: 13.44
 to 13.56 volts per 6-cell battery)

Design Life: 10 years in float applications
 at 77°F (25°C)


Dimensions: 10.20" (259 mm) L
 x 6.56" (166 mm) W
 x 8.24" (209 mm) H

Weight: 61 lbs. (27.7 kg)

DISCHARGE RATE IN WATTS PER CELL RATINGS @ 77°F (25°C)†

Volts Per Cell (VPC)	1 MIN.	5 MINS.	10 MINS.	15 MINS.	20 MINS.	30 MINS.	40 MINS.	50 MINS.	60 MINS.
1.60	1080	610	413	316	259	190	151	124	107
1.67	972	576	400	310	254	188	149	123	106
1.70	924	559	393	305	250	185	148	122	105
1.75	830	519	373	293	243	182	145	120	104
1.80	—	466	343	277	235	176	140	116	101

† Subject to change without notice.



EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4781

Order Department Hotline: 610-682-4231

www.eastpennunigy.com • e-mail: sales@eastpennunigy.com

E.P.M. Form No. 2008 7/13 © 2013 by EPM Printed in U.S.A.

All data subject to change without notice.
No part of this document may be copied or reproduced, electronically or mechanically, without written permission from the company.